

LORA ENABLED ALARM FOR SMART CITY

Sagar J Poojary^{1*}, Arun M L², Tharun S³, M D Afzal⁴, Anshu Deepak⁵

1

¹Department of Electronics and Communication Engineering, R. R. Institute of Technology, Karnataka, India

²Department of Electronics and Communication Engineering, R. R. Institute of Technology, Karnataka, India

³Department of Electronics and Communication Engineering, R. R. Institute of Technology, Karnataka, India

⁴Department of Electronics and Communication Engineering, R. R. Institute of Technology, Karnataka, India

⁵Department of Electronics and Communication Engineering, R. R. Institute of Technology, Karnataka, India

*Corresponding Author Email: sagarjpoojary6@gmail.com

Abstract

This paper presents the design and implementation of a Wireless Sensor Monitoring System using ESP32 microcontroller and Internet of Things (IoT) technology. The proposed system provides wireless communication between sensor nodes and cloud based monitoring platforms using LoRa and Wi-Fi communication modules. The system is designed to collect environmental data such as temperature and moisture levels and transmit the information to mobile phones or laptops without the use of wired connections.

The system integrates Arduino, LoRa modules, ESP32 microcontroller, and sensors to achieve long range and low power wireless communication. Sensor data is collected using the DS18B20 temperature and moisture sensor and transmitted through LoRa communication to an ESP32 module connected to a Wi-Fi router. The received data is then uploaded to the cloud or displayed directly on connected devices.

The proposed model reduces installation cost, minimizes wiring complexity, and provides a modern digital monitoring solution for smart buildings and industrial applications. The system is reliable, cost effective, and suitable for real time monitoring applications.

Keywords- Education, Computer Graphics, Visual Depiction, Virtual Reality, Animation, Visual Effects

1. Introduction

The rapid development of Internet of Things (IoT) technology has transformed traditional monitoring systems into intelligent wireless communication systems. Conventional wired monitoring methods involve high installation cost, maintenance difficulties, and limited flexibility. Wireless sensor networks provide an efficient solution by enabling real time communication between devices without physical wiring. IoT based monitoring systems are widely used in industries, smart homes, agriculture, healthcare, and environmental monitoring applications. These systems allow users to monitor sensor data remotely through cloud servers or mobile devices.

This project focuses on developing a Wireless Sensor Monitoring System using ESP32 and LoRa communication technology. The proposed system

collects sensor data and transmits it wirelessly to remote devices using Wi-Fi and LoRa modules.

The system uses Arduino for sensor interfacing, LoRa modules for long range wireless transmission, and ESP32 for cloud connectivity. The implementation aims to reduce wiring complexity, lower installation cost, and improve monitoring efficiency.

2. Related Work

Wireless sensor networks have gained significant importance in recent years due to their low power consumption, scalability, and flexibility. IoT based monitoring systems are commonly used for environmental sensing and industrial automation.

Traditional wireless systems mainly relied on Bluetooth and ZigBee communication, which provide limited transmission range. LoRa technology has emerged as an effective alternative because of its

long communication range and low power requirements. ESP32 microcontrollers are widely used in IoT applications because of their built-in Wi-Fi capability, low cost, and high processing performance. Several research works have demonstrated the use of ESP32 and LoRa for real-time environmental monitoring systems.

Modern IoT systems integrate cloud computing with wireless communication to provide remote access and real-time monitoring through smartphones and computers.

The rapid proliferation of Wireless Sensor Networks (WSNs) represents a profound shift in data acquisition, driven by structural advancements in micro-electromechanical systems and low-power semiconductor technologies.

In contemporary industrial and ecological contexts, WSNs serve as the primary sensory layer for the Internet of Things (IoT), enabling the dense deployment of autonomous, spatially distributed nodes that continuously sample physical and environmental conditions. The widespread adoption of these networks is fundamentally tied to their inherent resource-efficient architecture, massive scaling capabilities, and exceptional deployment flexibility. Minimal energy demands allow standalone hardware nodes to operate continuously for years on small batteries or localized energy-harvesting cells without intervention.

Furthermore, dynamic architectural layouts allow networks to seamlessly expand by integrating hundreds of new physical tracking points without causing service disruptions or requiring a structural overhaul of the central infrastructure.

This absence of physical cabling eliminates traditional installation bottlenecks, letting teams deploy ruggedized hardware into inaccessible, hazardous, or dynamically changing physical environments. Consequently, these networks have evolved from simple telemetry arrays into highly adaptive systems used for automating complex industrial manufacturing pipelines and tracking localized ecological shifts. In modern manufacturing facilities, they monitor vibration and thermal anomalies in heavy machinery to facilitate predictive maintenance, while in ecological monitoring, they track macro-level climate shifts, precision agriculture metrics, and early-stage forest fires.

Historically, early wireless monitoring systems relied heavily on short-range communication protocols, most notably Bluetooth Low Energy and ZigBee. While these legacy frameworks excel in personal area networks and localized smart-home automation due to their high data rates, they exhibit severe operational boundaries when scaled to expansive geographic or industrial zones. The primary bottleneck is limited transmission range, as these architectures typically suffer from a restricted effective radius that degrades rapidly in the presence of physical obstructions, concrete structures, or dense foliage. High-frequency signals at two-point-four gigahertz experience intense path loss and multi-path fading, and attempting to bridge vast distances with these technologies requires dense multi-hop mesh routing that exponentially increases network overhead, introduces packet latency, and rapidly drains node batteries. To resolve this bottleneck, the IoT industry shifted toward Low-Power Wide-Area Network (LPWAN) standards, with LoRa technology emerging as a highly effective alternative due to its long communication range and low power requirements. Operating in unlicensed sub-gigahertz radio bands, LoRa utilizes chirp spread spectrum modulation to achieve superior building penetration and miles of coverage. This modulation technique provides exceptional link budget characteristics, allowing signals to be decoded even when their power falls well below the local thermal noise floor. Because LoRa end-nodes remain in low-power deep-sleep modes and only activate to transmit small data payloads at scheduled intervals, their energy consumption remains strictly controlled, directly resolving the trade-off between long-distance telemetry and extended battery longevity.

3. Methodology

The primary layer of the architecture is the sensor node, which is deployed to capture real-time microclimate shifts from the localized environment. This system utilizes a DS18B20 digital thermometer probe alongside matching moisture detection elements to reliably capture ambient metrics. Operating on a high-precision, proprietary 1-Wire communication protocol, the DS18B20 sensor achieves precise temperature tracking across varying thermal thresholds while occupying only a single digital input-output pin on the controller board.

The accompanying moisture detection assembly continuously quantifies water volume variances within the immediate surrounding medium. By relying on this specialized, low-overhead hardware layer, the system performs ongoing, automated data collection directly at the physical tracking source. This continuous capture provides a steady influx of physical metrics, forming the baseline data stream needed to drive all subsequent telemetry and edge processing calculations.

Once the raw environmental data is captured, it is instantly routed to an ATmega-based Arduino microcontroller board, which serves as the core local computing hub. The Arduino processing framework functions as an intermediate signal-conditioning step to bridge the gap between physical sensor outputs and long-range communication links. The onboard hardware reads incoming analog signals and routes them through its internal multi-channel Analog-to-Digital Converter peripheral. This process transforms fluctuating analog voltages into structured, high-resolution digital data words. Beyond executing this digital translation, the central processing unit organizes the raw sensor metrics into standardized data payloads. This systematic sorting strips away ambient signal noise, creates uniform packet structures, and prepares the formatted data arrays for immediate handover to the primary long-range wireless transmitter.

The digital data arrays are then handed over to an integrated LoRa communication module via an SPI interface to prepare for over-the-air transmission. The LoRa module serves as a long-range physical-layer transmitter, converting the digital data payloads into robust radio frequency packets. By utilizing sub-gigahertz chirp spread spectrum modulation, the radio hardware achieves high link budgets and excellent resistance to signal noise.

4. Results and Discussion

The physical build of the tracking grid relies on a dual-stage hardware architecture that uses specialized components to collect and transmit data over long distances. At the edge layer, an Arduino development board acts as the direct interface for the sensors, while an ESP32 System-on-Chip functions as a high-performance receiving gateway. Local data collection is handled by high-precision

DS18B20 digital thermal sensors, which are wired into the microcontrollers.

This specialized directional antenna focuses the incoming signals, reduces interference, and allows the system to pull in clear data packets from remote sensors located kilometers away. Finally, an onsite wireless network router completes the hardware stack, providing the local internet connection the gateway needs to upload its data.

The final stage of the data pipeline handles network routing and real-time remote data storage. Once the ESP32 gateway receives the radio packets via its LoRa interface, its internal firmware executes parsing scripts to extract the sensor readings and verify data integrity.



Fig1: Temperature alert notifications generated in Blynk



Fig2: Blynk Dashboard displaying ESP32-DHT Sensor data.

This specialized modulation allows the transmitter to broadcast the data packets over vast geographic expanses, easily bypassing dense concrete structures, thick foliage, and terrain barriers. By avoiding the severe transmission distance limitations of

traditional short-range networks, this module acts as a highly resilient telemetry bridge, allowing field-deployed sensor arrays to maintain a stable connection with remote monitoring stations located kilometers away.

At the receiving end of the long-range radio link, an ESP32 System-on-Chip board functions as an intelligent, hybrid edge gateway. The ESP32 is equipped with an integrated LoRa radio receiver module alongside native dual-wireless connectivity, allowing it to act as an agile network router. The dual-core processor captures the incoming sub-gigahertz radio packets, extracts the compressed digital sensor data, and performs initial formatting checks. Once validated, the microcontroller activates its built-in twenty-four- gigahertz Wi-Fi radio stack to establish a secure network connection with a local internet router. By bridging two distinct wireless protocols, the ESP32 gateway seamlessly transitions the data from a localized radio network into standard TCP/IP packets, paving the way for immediate upstream internet transmission.



Fig3: ESP32 and DHT Sensor Interfacing Circuit.

The final stage of the data pipeline handles global data ingestion, long-term storage, and end-user visualization. The internet-connected gateway uses lightweight protocols like MQTT or HTTP RESTful APIs to upload the compiled data packets directly to a cloud server or an open IoT broker platform. Within the cloud infrastructure, the incoming metrics enter time-series databases for secure logging, historical trend analysis, and predictive evaluation loops. Simultaneously, the cloud engine exposes these data feeds to remote user interfaces, allowing information to be viewed on smartphones, tablets, and laptops. Long-range data transmission is managed by matching LoRa transceivers linked to each processing unit. To maximize transmission efficiency and maintain a stable radio link over long

distances, the receiving gateway is fitted with a high-gain patch panel antenna.

The microcontroller then boots its native wireless network stack, handles security handshakes, and connects to the onsite Wi-Fi router. This connection bridges the local sensor network with the wider internet, letting the ESP32 upload the sensor data to remote cloud servers using lightweight IoT messaging protocols. To guarantee uninterrupted service in remote deployments, the software layer incorporates robust error-handling routines and proactive power-management strategies.

The edge firmware utilizes hardware watchdog timers that automatically reset the microcontrollers if a software hangs or sensor failure is detected.

5. Conclusion

This paper details the successful architecture, implementation, and empirical validation of a high-efficiency Wireless Sensor Monitoring System driven by an ESP32 microprocessor and cutting- edge IoT paradigms. The engineered system achieves seamless, end-to-end wireless telemetry by combining long-range radio infrastructure with high-bandwidth local internet backhauls. Field- deployed sensor arrays transmit localized environmental data using robust LoRa communication links, which are then captured by an edge gateway and routed through high-speed Wi-Fi networks. This hybrid design ensures that raw physical data is reliably moved from isolated field locations across wide geographic zones and onto standard internet networks without packet degradation.

By integrating Arduino microcontrollers, ESP32 modules, and LoRa transceivers into a unified hardware pipeline, this design provides an exceptionally reliable and cost-effective monitoring framework for time-critical applications.

This specialized layout delivers substantial cost savings over traditional telemetry networks by eliminating expensive physical cabling and reducing the labor needed for onsite setups. By stripping away complex wired infrastructures, the system avoids common structural failure points like cable degradation, grounding loops, and physical port damage. This reduction in hardware complexity yields a highly resilient, plug-and-play monitoring solution that significantly lowers both upfront

installation costs and long-term maintenance overhead.

The final prototype highlights the transformative potential of combining IoT architectures with distributed wireless sensor networks to drive modern automation pipelines and smart monitoring grids. Beyond serving as a functional proof of concept, this model provides a scalable blueprint for building smarter municipal, agricultural, and industrial infrastructure. Future development phases will focus on expanding the network's capabilities by implementing advanced cryptographic protocols to improve data security and authentication across open channels. Additionally, integrating ultra-low-power sleep cycles and dynamic mesh routing protocols will further boost data transmission efficiency and expand the network's scaling capacity to support thousands of active concurrent nodes.

To guarantee uninterrupted service in remote deployments, the software layer incorporates robust error-handling routines and proactive power-management strategies. The edge firmware utilizes hardware watchdog timers that automatically reset the microcontrollers if a software hang or sensor failure is detected, preventing the nodes from locking up indefinitely in the field. To maximize battery longevity, the Arduino and ESP32 chips are programmed to enter ultra-low-power deep-sleep modes immediately after a data transmission is completed, shutting down non-essential internal peripherals until the next scheduled sampling interval. Furthermore, the communication scripts include cyclic redundancy checks (CRC) and basic data-validation filters to automatically drop corrupted packets caused by ambient RF noise.

References

- [1]M. A. Al-Khafaji and A. H. Ali, "Performance evaluation of LPWAN standards: A comparative study of LoRa, ZigBee, and BLE for long-range industrial telemetry," *IEEE Internet of Things Journal*, vol. 11, no. 4, pp. 841– 853, February 2024.
- [2]S. T. Ahmed, R. Khan, and M. S. Ibrahim, "A scalable and energy-efficient LoRaWAN-based geofencing system for remote microclimate tracking," *IEEE Access*, vol. 12, pp. 48539–48551, April 2024.
- [3]J. M. Gomez, R. L. Santos, and T. H. Kim, "Resilient edge- gateway design: Synergistic integration of ESP32 and sub-gigahertz LoRa transceivers for data fusion," *International Journal of Wireless Information Networks*, vol. 31, no. 2, pp. 195–208, June 2024.
- [4]K. B. Nair and V. P. Sharma, "Real-time environmental parameters monitoring using ESP32 system-on-chip and HPD13A-SX1276 LoRa modules," *IEEE Transactions on Instrumentation and Measurement*, vol. 73, pp. 1102–1115, January 2024.
- [5]L. Zhang, H. Wang, and Y. Liu, "High-precision agricultural telemetric grids using 1-Wire DS18B20 thermal probes and directional patch panel antennas," *IEEE Sensors Journal*, vol. 23, no. 18, pp. 21045–21054, September 2023.
- [6]R. Pawar and P. Tawashe, "Prototyping sensor infrastructures: Interconnection optimization and wiring reduction models using microcontrollers," *Proceedings of the National Conference on Science, Technology, Engineering and Management (NCSTEM)*, pp. 310–316, April 2023.
- [7]E. C. Peterson and D. R. Mitchell, "Embedded C optimization for low-power wide-area networks within the open- source Arduino IDE framework," *Software: Practice and Experience*, vol. 54, no. 3, pp. 423–439, March 2024.
- [8]A. B. Cruz, M. J. Silva, and F. A. Rodriguez, "Fault-tolerant data pipelines: Time-series database ingestion and failover routing strategies for ESP32 gateways," *IEEE Transactions on Cloud Computing*, vol. 13, no. 1, pp. 114–127, January 2025.
- [9]H. T. Nguyen and M. K. Rahman, "Design and study of LoRa- based IIoT networks for modern industrial automation and scalable environmental sensing," *IEEE Transactions on Industrial Informatics*, vol. 21, no. 2, pp. 1432–1443, January 2025.
- [10]N. K. Mishra and S. Atkale, "The potential of distributed wireless sensor ecosystems in smart infrastructure: A roadmap for security and efficiency," *Journal of Network and Computer Applications*, vol. 234, article 103812, March 2025.