

Design and Implementation of an Automatic Rain Sensing Wiper System Using Arduino for Enhanced Driving Safety

Aruna Jacintha T¹, Sahana C², Shree Vani K³, Thanushree S^{4*}, Yashwanth S⁵

¹Department of Electronic & Communication Engineering, R R Institute Of Technology, Karnataka, India.

²Department of Electronic & Communication Engineering, R R Institute Of Technology, Karnataka, India.

³Department of Electronic & Communication Engineering, R R Institute Of Technology, Karnataka, India.

⁴Department of Electronic & Communication Engineering, R R Institute Of Technology, Karnataka, India.

⁵Department of Electronic & Communication Engineering, R R Institute Of Technology, Karnataka, India.

*Corresponding Author Email: thanushreethanu40@gmail.com

Abstract

Rain sensing wiper systems are a useful feature in modern vehicles that help improve both driver comfort and safety. Instead of the driver having to manually adjust the wiper speed during changing weather conditions, the system automatically detects rain on the windshield and responds accordingly. This is especially helpful during sudden or uneven rainfall, where constant manual adjustment can be distracting. In this paper, we present the design and implementation of a rain sensing wiper system that makes use of sensors, a microcontroller, and simple control logic. The sensor is placed in a position where it can detect water droplets on the windshield surface. Once rain is detected, the system processes the input and adjusts the speed of the wipers based on how heavy the rainfall is. For light rain, the wipers move slowly, while for heavier rain, the speed increases automatically. The system was tested under different conditions, and the results show that it responds quickly and works efficiently. Compared to traditional manually operated wipers, this approach reduces the need for driver intervention and helps maintain better visibility, making driving safer and more convenient.

Keywords—Rain sensor, windshield wiper, automation, embedded system, automotive electronics

1. Introduction

In recent years, the automotive industry has focused heavily on improving safety, comfort, and automation. One critical factor for safe driving is clear visibility, especially during rainy conditions. Rainfall can obstruct the driver's view, increasing the chances of accidents. In conventional systems, drivers must manually turn on the wipers and adjust their speed based on If applicable, include funding details here. Otherwise, remove this section rain intensity. This not only becomes inconvenient but can also distract the driver, particularly during sudden or varying rainfall. To overcome this limitation, rain sensing wiper systems have been developed as an automated solution. These systems are designed to detect rain on the windshield and activate the wipers without

requiring any manual input. By doing so, they help maintain clear visibility while allowing the driver to

stay focused on the road. The system works by using sensors to detect water droplets on the windshield.

Commonly, either optical sensors or resistive sensors are used. Optical sensors detect changes in reflected infrared light when rain is present, while resistive sensors measure changes in electrical resistance caused by water. The sensor data is then processed by a microcontroller, which determines the intensity of rainfall and adjusts the wiper speed accordingly—ranging from intermittent wiping for light rain to continuous high-speed operation for heavy rain. This automatic response reduces driver distraction and ensures quick action during unexpected weather changes. As a result, the system significantly improves

safety and driving comfort. With the increasing demand for smart and automated vehicle features, rain sensing wipers have become an important part of modern automotive design. They also demonstrate the effective use of embedded systems in real-world applications.

2. Related Work

Several researchers have worked on improving rain sensing wiper systems using different technologies and approaches. Early work by Paramasivam and Priya [1] focused on simple automatic systems that detect rain and activate wipers without driver input, improving both convenience and safety. Kumar and Patel [2] further enhanced this concept using microcontroller-based designs, which provided better accuracy and faster response. More advanced systems, such as the ARM-based design by Mohan and Deepak [3], demonstrated how improved processing capability can increase detection efficiency. Different sensing techniques have also been widely explored in the literature. Optical sensors using infrared technology, as discussed by Wu and He [4], provide high accuracy and reliability in detecting rainfall. Computer vision techniques introduced by Diaz and Contreras [5] enable intelligent detection of rain and fog, improving environmental awareness. IoT-based systems developed by Karthik and Rajan [6] allow real-time monitoring and data logging, making the system more efficient and connected. Other approaches include capacitive sensing methods [7] and embedded automotive modules [8], which offer improved flexibility and performance in different operating conditions. Systems integrating additional features such as automatic headlight control [9] further enhance vehicle safety. Arduino-based implementations [10] provide simple, low-cost, and effective solutions, making them suitable for small-scale and educational applications.

3. Materials and Methods

The rain sensing wiper system is designed using a simple combination of a sensor, a microcontroller, and a motor mechanism. The aim is to automatically detect rain and control the wiper speed without requiring any manual action from the driver. The system mainly consists of a rain sensor, an Arduino microcontroller, and a servo motor. The sensor detects water on its surface and produces an analog signal. This signal is processed by the microcontroller, which decides how the wiper should operate.

Sensor Operation A resistive rain sensor is used in this project because it is simple and cost-effective.

When water droplets fall on of the proposed system




Fig. 1. Block diagram

the sensor, the resistance decreases and the output voltage changes. To make the system reliable, the sensor was tested under different conditions such as dry surface, light rain, and heavy rain. Data The sensor output is connected to the analog pin of the Arduino. The analog signal is converted into digital values (0–1023). These values indicate the level of moisture present on the sensor. A servo motor is used to simulate the wiper movement. The motor rotates back and forth to create the wiping action.




Fig. 2. Flowchart of system operation

The rain sensing wiper system works by automatically detecting the presence of water on the sensor surface and controlling the wiper accordingly. The system continuously monitors environmental

conditions and responds in real time without any manual input. A resistive rain sensor is used to detect water droplets. When the sensor surface is dry, it offers high resistance. As soon as water droplets fall on it, the resistance decreases due to the formation of conductive paths.

The sensor output is given to the analog input of the Arduino microcontroller. The built-in ADC converts this analog signal into a digital value ranging from 0 to 1023. Lower values indicate higher moisture levels, while higher values represent dry conditions. The microcontroller continuously reads the sensor value and compares it with predefined thresholds. Based on this comparison, it determines the intensity of rainfall.

- Dry condition: Wiper remains OFF
- Light rain: Slow wiping
- Moderate rain: Medium speed
- Heavy rain: Fast wiping

Once the rain intensity is identified, the microcontroller sends control signals to the motor. In this prototype, a servo motor is used to simulate the wiping action. The motor rotates back and forth to mimic the movement of a real wiper. The speed of this motion depends on the detected rainfall intensity. As the wiper clears the water, the sensor detects a reduction in moisture. The microcontroller updates the output accordingly. When the surface becomes dry, the system automatically turns off the wiper. The rain sensor detects water droplets on its surface and produces an analog output proportional to moisture level.

A microcontroller (such as Arduino or similar) processes sensor data and generates control signals. The motor driver circuit controls the speed of the wiper motor based on signals from the microcontroller. The wiper motor performs the physical wiping action on the windshield.

The rain sensing wiper system can be used in a wide range of applications where automatic rain detection is required. It is mainly used in automobiles such as cars, buses, and trucks to automate windshield wiper operation and improve driving comfort. The system can also be integrated into smart vehicles as part of advanced automation features, contributing to

improved safety systems. Apart from road vehicles, the system can be applied in railway systems to maintain clear visibility for train drivers during rainy conditions. It is also useful in agricultural vehicles and outdoor machinery that operate in open environments. In industrial settings, the system can be used in equipment exposed to weather conditions. Furthermore, it can be extended to IoT-based environmental monitoring systems, where rain detection plays an important role in data collection and automation.

A. Software Implementation

The system is programmed using Arduino IDE. The micro controller continuously reads the sensor value and updates the motor operation accordingly .
[language=C, caption=Arduino code for automatic wiper control] include <Servo.h> Servo wiperServo; const int rainPin = A0;

```
void setup() wiperServo.attach(9);

void loop() int value = analog Read(rainPin);

if (value < 300) wiperServo. Write (120);

if (value < 600) wiperServo. Write (80); //
medium else

wiperServo. Write (0); // off

delay (200)
```

4. Results and Discussion

The performance of the rain sensing wiper system was evaluated under different environmental conditions to understand its accuracy, response time, and overall reliability. The system was tested by manually simulating rainfall using water droplets of varying intensity on the sensor surface.

A. Test Setup

The experimental setup consisted of a rain sensor module connected to an Arduino microcontroller, along with a servo motor to simulate the wiper action. A controlled amount of water was applied to the sensor to represent light, moderate, and heavy.n.



Fig. 3. Experimental setup used for testing the system

A. Sensor Response Analysis

The rain sensor produced different analog values depending on the amount of water present on its surface. It was observed that higher moisture levels resulted in lower analog values, while dry conditions produced higher values. These readings were consistent across multiple trials, showing that the sensor was able to reliably detect variations in rainfall intensity. Minor fluctuations were observed due to uneven distribution of water droplets, but they did not significantly affect system performance.

B. Wiper Response and Control

Based on the sensor input, the microcontroller successfully categorized the rainfall into different levels and controlled the wiper speed accordingly.

TABLE I

SENSOR VALUE VS WIPER ACTION

Condition	Sensor Value	Wiper Action
Dry	>600	OFF
Light Rain	300-600	Slow Wipe
Heavy Rain	<300	Fast Wipe

C. Response Time

The overall response time of the system was found to be very fast. The sensor detected the presence of water almost instantly, and the microcontroller processed the input within a few milliseconds. The total system response, including motor activation, was observed to be less than 200 ms. This quick response ensures that the wiper activates without

noticeable delay, which is important for maintaining visibility during sudden rainfall.

D. Accuracy and Reliability

The system showed high accuracy in detecting moderate and heavy rainfall conditions, with consistent wiper activation in all trials. In the case of very light rain, slight delays were observed due to minimal water contact on the sensor surface. However, this behavior is acceptable for a low-cost prototype. The system also demonstrated stable

operation during continuous testing. No unexpected resets or abnormal motor behavior were observed, indicating good reliability

E. Limitations

Although the system performed well, some limitations were identified. The resistive sensor is sensitive to dirt, dust, and water accumulation, which can sometimes affect accuracy. In addition, the system does not differentiate between rain and other forms of moisture such as condensation.

F. Future Scope

In future, the system can be enhanced by using optical sensors instead of resistive sensors. Optical sensors are more accurate and less affected by dirt or corrosion, which improves long-term reliability.

The system can also be integrated with a DC motor and motor driver circuit instead of a servo motor to make it suitable for real automotive applications.

This would allow better control over speed and torque. Another possible improvement is the use of adaptive control techniques such as fuzzy logic or machine learning. These methods can help the system adjust more intelligently to changing rain patterns and reduce unnecessary wiper movements.

5. Conclusion

In this work, a simple and effective rain sensing wiper system was designed and implemented using a resistive rain sensor and an Arduino microcontroller. The system was able to automatically detect the presence of rain and control the wiper movement without any manual input. From the results, it is clear that the system responds quickly to changes in moisture and adjusts the wiping speed accordingly.

The overall performance was stable, and the system worked reliably under different testing conditions. One of the main advantages of this design is its simplicity and low cost, which makes it suitable for small-scale applications and educational purposes. At the same time, it demonstrates how basic sensors and embedded systems can be used to solve real-world problems. Although the system performs well, there is still room for improvement in terms of sensor accuracy and advanced control techniques. With further development, this system can be extended for use in real vehicles..

References

- [1] S. Paramasivam and R. Priya, "Automatic rain sensing wiper system," *International Journal of Engineering Research*, vol. 4, no. 5, pp. 234–238, 2019.
- [2] A. Kumar and P. Patel, "Microcontroller based automatic wiper control system," *IEEE Conference on Smart Systems*, pp. 112–116, 2020.
- [3] S. Mohan and D. Deepak, "ARM based rain detection and wiper automation," *International Conference on Embedded Systems*, pp. 89–93, 2018.
- [4] J. Wu and L. He, "Optical rain sensor using infrared technology for automotive applications," *IEEE Sensors Journal*, vol. 17, no. 6, pp. 1785–1792, 2017.
- [5] M. Diaz and P. Contreras, "Rain and fog detection using computer vision techniques," *IEEE Access*, vol. 6, pp. 40500–40510, 2018.
- [6] R. Karthik and S. Rajan, "IoT based smart wiper control system," *International Journal of IoT Applications*, vol. 3, no. 2, pp. 45–50, 2021.
- [7] P. Chakrabarti and H. Kaur, "Capacitive sensor for rainfall detection," *IEEE Sensors Conference*, pp. 220–224, 2019.
- [8] V. Singh and A. Mehta, "Embedded rain sensing module for automotive safety," *International Journal of Electronics*, vol. 10, no. 3, pp. 150–155, 2020.
- [9] N. Nandhini and R. Rakesh, "Automatic rain sensing wiper and headlight control system," *International Conference on Automation*, pp. 301–305, 2021.
- [10] A. Sahu and S. Patil, "Arduino based rain detection system," *International Journal of Engineering Trends*, vol. 5, no. 4, pp. 210–214, 2019.